



TN300W Series Powder Free (9.5")

TechNiGlove 9.5" powder free nitrile gloves are puncture resistant and 100% nitrile, reducing the potential for allergic reactions to natural rubber proteins.



Specifications

Technical Properties		Physical Properties	
Particle Levels Class M3.5 (100)	<3000 total particle/cm2 > 0.5um IEST- RP-CC005.2 Method	Style	Ambidextrous
Flouride	< 0.05 ug/cm2	Length	9.5" (240mm)
Chloride	< 3.0 ug/cm2	Thickness	5 mil (0.005")
Nitrite	< 0.05 ug/cm2	Grip Surface	Microtextured Fingertips
Nitrate	< 3.00 ug/cm2	Sizes	XS-XXL
Phosphate	< 0.05 ug/cm2	Cuff	Beaded
Sulphate	< 3.00 ug/cm2	Colors	White
Total NVR (DI Water)	< 8.00 ug/cm2	Tensile Strength	>12.5 MPa
ESD Properties	At 50-60% Humidity	Elongation at break (%):	>500
Surface Resistivity	< 10-10 ohm/square per ESD-S11.11	Ordering Information	
Static Decay	< .5 seconds per RETS-5-003	TN300(W)	X-SMALL 20 lbs.
Cert of Conformance	Available on request	TN301(W)	SMALL 20 lbs.
		TN302(W)	MEDIUM 21 lbs.
		TN303(W)	LARGE 21 lbs.
		TN304(W)	X-LARGE 22 lbs.
		TN305(W)	XX-LARGE 23 lbs.

100 gloves/polybag, 10 polybags/case

All TechNiGlove products are manufactured in ISO9001:2000 and ISO 14001:2004 certified facilities

To Order Call:
Harmony Business Supplies
 1-800-899-1255
www.HarmonyCR.com